



T N U X



Shape



Clearance Angle



Tolerance
 $d \pm 0.08$
 $m \pm 0.13$
 $s \pm 0.13$



Fixing
 Chip breaker

Insert Designation	Grade	l	s	r	Catalog Nr.
TNUX 160404 R	LT 1000	16	4.76	0.4	T0001938
TNUX 160404 L	LT 1000	16	4.76	0.4	T0002794
TNUX 160408 R	LT 1000	16	4.76	0.8	T0001939
TNUX 160408 L	LT 1000	16	4.76	0.8	T0002795

60° Triangle shape inserts. Suitable for general Turning and longitudinal operations, where there is a concern for work piece vibrations.

Application Guide

	Finishing	Medium	Roughing / Interrupted cut	
TNUX 160404 R	😊	😐	😞	😊 = Good 😐 = Acceptable 😞 = Not recommended Finishing: d.o.c. = 0.30 - 1.50 mm fn = 0.08 - 0.20 mm/rev Medium: d.o.c. = 0.70 - 4.50 mm fn = 0.15 - 0.45 mm/rev Roughing d.o.c. = 3.00 - 7.00 mm fn = 0.35 - 0.70 mm/rev
TNUX 160404 L	😊	😐	😞	
TNUX 160408 R	😐	😊	😐	
TNUX 160408 L	😐	😊	😐	

Feed x d.o.c.
 =
 Amax

$V_c \Rightarrow$
 Productivity

Machine Recommendations Guide. Details on page 10

TNUX 160404 R&L LT 10 & LT 1000

Material Group	Gr. N°	VDI Group	Material Examples*	Hardness	D.O.C. [mm]		Feed [mm/rev]		Amax [mm²]	V _c [m/min]		Optimal cutting conditions					
					min	max	min	max		min	max	D.O.C.	Feed	V _c			
Steel	Non-alloyed	1	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.2	3.0	0.11	0.23	0.60	180	330	2.0	0.18	300			
		2		190 HB		2.5		0.22	0.52		280			260			
		3		250 HB		2.5		0.20	0.48		250			240			
	Low alloyed	2	42CrMo4, S150, Ck60, 4140, 4340, 100Cr6	180 HB	0.2	2.5	0.10	0.20	0.50	120	280	2.0	0.15	260			
		4,6		230 HB		2.5		0.20	0.48		250			240			
		5,7		280 HB		2.0		0.18	0.40		210			200			
		8		350 HB		2.0		0.18	0.36		180			180			
	High alloyed	3	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.2	2.5	0.09	0.18	0.40	70	190	2.0	0.12	180			
		10		280 HB		2.5		0.16	0.40		150			140			
		11		320 HB		2.0		0.14	0.32		130			120			
		11		350 HB		2.0		0.14	0.26		110			110			
Stainless Steel	Austenitic	4	304, 316, X5CrNi18-9	180 HB	0.2	2.5	0.10	0.18	0.32	170	270	2.0	0.12	260			
		14		240 HB		2.5		0.18	0.26		160			220	210		
	Duplex	5	X2CrNi23-4, S31500	290 HB	0.2	2.0	0.09	0.14	0.20	80	150	2.0	0.12	140			
		14		310 HB		2.0		0.14	0.20		70			140			
	Ferritic & Martensitic	6	410, X6Cr17, 17-4 PH, 430	200 HB	0.2	2.5	0.10	0.18	0.32	170	250	2.0	0.15	240			
		13		42 HRc		2.0		0.16	0.26		120			190	180		
Cast Iron	Grey	7	GG20, GG40, EN-GJL-250, No30B	150 HB	0.2	3.0	0.08	0.20	0.64	170	250	2.0	0.18	240			
		15		200 HB		3.0		0.20	0.60		160			230	220		
		16		250 HB		3.0		0.20	0.60		150			210	200		
	Malleable & Nodular	8	GGG40, GGG70, 50005	150 HB	0.2	2.5	0.08	0.18	0.48	120	250	2.0	0.15	240			
		17,19		200 HB		2.5		0.18	0.40		230			220			
		18,20		250 HB		2.5		0.18	0.40		190			180			
High Temp. Alloys	Fe, Ni & Co based	9	Incoloy 800, Inconel 700, Stellite 21	240 HB	0.2	2.0	0.09	0.15	0.26	25	50	2.0	0.12	40			
		33		250 HB		2.0		0.15	0.26		25			50	40		
		34		350 HB		2.0		0.15	0.26		23			45	35		
	Ti based	10	TiAl6V4, T40	-	0.2	2.0	0.09	0.16	0.32	45	65	2.0	0.15	60			
		37		-		2.0		0.14	0.26		35			60	50		
	Hardened Mat.	Steel	11	X100CrMo13, 440C, G-X260NiCr42	45 HRc	0.2	1.8	0.05	0.12	0.20	50	100	1.5	0.11	90		
38			50 HRc		1.5		0.10		0.17	40		90			1.2	0.09	80
38			55 HRc		1.4		0.09		0.13	40		80			1.0	0.07	70
Chilled Cast Iron		40	Ni-Hard 2	400 HB	0.2	1.6	0.05	0.12	0.17	40	60	1.2	0.11	50			
White Cast Iron		41	G-X300CrMo15	55 HRc	0.2	1.4	0.05	0.09	0.13	30	50	1.0	0.07	40			
NF	Al (>8%Si)	12	25	AlSi12	130 HB	0.2	4.0	0.10	0.30	0.70	200	400	2.0	0.20	350		

TNUX 160408 R&L LT 10 & LT 1000

Material Group	Gr. N°	VDI Group	Material Examples*	Hardness	D.O.C. [mm]		Feed [mm/rev]		Amax [mm ²]	V _c [m/min]		Optimal cutting conditions						
					min	max	min	max		min	max	D.O.C.	Feed	V _c				
Steel	Non-alloyed	1	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.5	5.0	0.21	0.50	1.80	180	280	3.0	0.35	240				
		190 HB		5.0		0.50		1.80						250	220			
		250 HB		5.0		0.45		1.50						250	200			
	Low alloyed	2	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	180 HB	0.5	5.0	0.21	0.45	1.20	120	280	3.0	0.32	200				
		230 HB		4.0		0.45		1.20						250	180			
		280 HB		4.0		0.18		0.40						1.20	210	150		
		350 HB		3.5		0.18		0.40						1.00	180	130		
	High alloyed	3	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.5	4.0	0.18	0.40	1.20	70	150	2.5	0.30	140				
		280 HB		4.0		0.35		0.80						130	120			
		320 HB		3.0		0.35		0.80						110	100			
		350 HB		3.0		0.35		0.80						110	90			
Stainless Steel	Austenitic	4	304, 316, X5CrNi18-9	180 HB	0.5	5.0	0.20	0.40	1.20	170	270	3.0	0.35	190				
		240 HB		5.0		0.40		1.00						160	220	170		
	Duplex	5	X2CrNiN23-4, S31500	290 HB	0.5	4.0	0.18	0.35	0.80	80	150	2.5	0.28	100				
		310 HB		4.0		0.35		0.80						70	140	90		
	Ferritic & Martensitic	6	410, X6Cr17, 17-4 PH, 430	200 HB	0.5	5.0	0.22	0.40	1.00	170	250	3.0	0.32	190				
		42 HRc		4.0		0.40		1.00						120	190	130		
Cast Iron	Grey	7	GG20, GG40, EN-GJL-250, No30B	150 HB	0.5	5.0	0.15	0.60	2.00	170	250	3.0	0.35	200				
		200 HB		5.0		0.60		1.80						160	230	180		
		250 HB		5.0		0.55		1.80						150	210	160		
	Malleable & Nodular	8	GGG40, GGG70, 50005	150 HB	0.5	5.0	0.15	0.50	1.50	120	230	3.0	0.30	180				
		200 HB		5.0		0.50		1.30						190	160			
250 HB	5.0	0.50	1.20	190	140	140												
High Temp. Alloys	Fe, Ni & Co based	9	Incoloy 800, Inconel 700, Stellite 21	240 HB	0.5	3.0	0.20	0.35	0.70	25	45	2.0	0.28	32				
		250 HB		3.0		0.35		0.70						25	45	30		
		350 HB		3.0		0.35		0.70						23	40	28		
	Ti based	10	TiAl6V4, T40	-	0.5	4.0	0.20	0.40	0.80	45	65	2.0	0.33	55				
		-		3.0		0.35		0.70						35	55	45		
Hardened Mat.	Steel	11	X100CrMo13, 440C, G-X260NiCr42	45 HRc	0.5	2.5	0.11	0.30	0.60	50	100	2.0	0.25	80				
		50 HRc		2.0		0.25		0.40						40	90	1.5	0.20	70
		55 HRc		1.5		0.20		0.30						40	80	1.0	0.18	60
	Chilled Cast Iron	40	Ni-Hard 2	400 HB	0.5	2.0	0.11	0.25	0.40	40	60	1.5	0.18	50				
	White Cast Iron	41	G-X300CrMo15	55 HRc	0.5	1.5	0.11	0.20	0.30	30	50	1.0	0.15	40				
NF	Al (>8%Si)	12	AlSi12	130 HB	0.5	6.0	0.20	0.60	1.80	200	400	3.0	0.40	280				